

## Technical Specifications

<b>Product Name</b>	<b>SwingPort™</b>
<b>Model Name</b>	Swing Port 1.0
<b>Type</b>	AS-99280
<b>Region</b>	EU, United States, Canada, Japan, Korea, China, Israel, Panama, Serbia, and Uruguay
<b>Manufacturer</b>	AutoStore AS
<b>Dimensions</b>	L: 1,411 mm / W: 1,606 mm / H: 1,100 mm
<b>Weight</b>	158.5 kg
<b>Weight Accuracy</b>	+/- 50g
<b>Max. Load Including Bin</b>	35 kg
<b>Bin Height Support</b>	220, 330, and 425 mm
<b>Max. Bin Throughput</b>	170 Bins/hr. with 8 m Bin Lift™ 2.0 Operator handling time of 15 seconds
<b>Min. Bin Exchange Time</b>	3 seconds
<b>Storage Temperature</b>	-25°C to +55 °C
<b>Operating Temperature</b>	+2°C to +35 °C
<b>Operating Humidity</b>	40 to 90% non-condensing
<b>Furniture Material</b>	Aluminum and composite material
<b>Working Height</b>	870 to 1,100 mm* * Static 1,000 mm working height for 425 mm Bin
<b>Noise Level</b>	<60 dBA
<b>Voltage</b>	100-240 VAC, 50-60 Hz
<b>Max. Current</b>	2 A
<b>Power Consumption</b>	90 W (normal operation)
<b>Power Connector</b>	C 13
<b>Signal</b>	<ul style="list-style-type: none"> <li>· Ethernet RJ45</li> <li>· External estop</li> </ul>
<b>IP Class</b>	IP20