

Technical Specifications

Product Name	VersaPort™ Wide VersaPort™ Narrow VersaPort™ Wide SDG VersaPort™ Narrow SDG
Model Name	PORT-AS-99600 PORT-AS-99602 PORT-AS-99601 PORT-AS-99603
Type	AS-99600 AS-99602 AS-99601 AS-99603
Region	Global
Manufacturer	AutoStore AS
Dimensions	Wide: L: 1,792 mm / W: 753 mm / H: 1,102 mm Narrow: L 2,387 mm / W: 533 mm / H: 1,102 mm
Weight	Wide: 108 kg (incl., frame) Narrow: 117 kg (incl., frame)
Weight Accuracy	+/- 100 g
Max. Load Including Bin	35 kg
Bin Height Support	220, 330, and 425 mm
Max. Bin Throughput	180 Bins/hr. on 16-level (330 mm Bins) 170 Bins/hr. on 18-level (330 mm Bins) 240 Bins/hr. on mezzanine level
Min. Bin Exchange Time	Wide: Weight function disabled: 7.5 s Weight function enabled: 9 s Narrow: Weight function disabled: 8.5 s Weight function enabled: 10 s
Storage Temperature	-25 °C to +55 °C
Operating Temperature	+1 °C to +35 °C
Operating Humidity	40 to 90 % non-condensing
Furniture Material	Aluminum and plastic material
Working Height	900 to 1,110 mm (25 mm increments)
Noise Level	< 70 dBA
Power	24 VDC, 5A Average: 100 W
Power Contact	Kycon KPJX-4S-S
Signal	Shielded Ethernet, RJ45
IP Class	IP20